

Portable table-type and hand-held benders for on-site work

DBD series benders are fast, accurate and easy to use: just set the bending angle and press the button.

DBD-25H 29





Our latest table-type bender is a heavy-duty model for rebars of up to 25mm (1") 620N/mm² tensile strength. It comes fully equipped with a set of nine bending rollers in a steel carrying case. Although intended primarily for on-site work, it is eminently suitable for the production shop.



















Both the DBD-25X and the smaller, lighter DBD-25L are prized field models because of their proven durability and ability to bend 25mm (1") 450N/mm² tensile strength rebars. For rebars of up to 20mm (3/4"), the DBD-19L is similarly treasured. Optional foot control, stand and bender covers are available for all three models.









SPECIFICATIONS					
Model	DBD-25H	DBD-25X	DBD-25L	DBD-19L	DBD-16L
Max.rebar diameter	25mm (1")			20mm (3/4")	16mm (5/8")
Bending speed	9 sec.	6 sec /180°	7 sec /180°	5 sec /180°	1.5 sec /180°
Max.tensile strength	620N/mm ²	560N/mm ²	490N/mm²		
Bending angle	Up to 180°				
Power supply	Single phase mains electricity / Generator				
Voltage	100V/115V/230V				
Power Input	1500W	1330W	1700W	1050W	
Weight	97 kg	86 kg	61 kg	40.8 kg	20 kg
Dimensions (mm)	540×580×440	490×550×440	462×320×415	320×425×415	320×350×245

Optional attachments: stand, footswitch

DBD-16L ©





This small unit may be carried in one hand but has all the attributes of its bigger brethren and can make a 180° bend in a 16mm(5/8") rebar in just 1.5 seconds.

